	3081	L.6L SPECIFICATIONS	
Model	308 1.6L models	Model	308 1.6L models
Engine	1.6 THP 150		Steering
Capacity	1598cc	Type	Variable electric power-assisted steering (with Park Assist capabillities)
Engine type		Turns lock-to-lock	3
Туре	Turbo-charged, all-alloy, inline 4 cylinder, with direct injection.	Minimum turning diameter - tyre (m)	10.4
Fuel	95 RON (PULP) or higher (recommended)	Wheels and tyres	
Bore x stroke (mm)	77 x 85.8	Rims	17 x 7J (Allure) 18 x 8J (Allure Premium)
Compression ratio		Tyres	225/45 R17 (Allure) 225/40 R18 (Allure Premium)
Max power		Body/exterior dimensions hatch (Touring)	
Petrol engine	110kW @ 5000rpm	Overall length (mm)	4253 (4585)
Max. torque (petro		Overall width (mm)	1804 (1863)
4-4-4	Transmission	Overall height (mm)	1457 (1472)
Туре	Six-speed automatic	Wheelbase (mm)	2620 (2730)
Gear Ratios (km/h per 100rpm)		Front track (mm)	1559
1st	9.2	Rear track (mm)	1533
2nd	17.7	` '	
3rd	28.1	Cd	0.28
4th	39.6		Weights/loads hatch (Touring)
5th	48.7	Kerb weight (kg)	1255 (1315)
6th 58.9		Capacities hatch (Touring)	
Final drive ratio	19/70	Fuel tank (L)	53
	Suspension	Seating	Five
Front	Psuedo MacPherson Strut, coil springs with hydraulic dampers	Boot Space (L)	Seats in place 435 (625) Seats folded 820L (1740)
Type Rear	Deformable crossmember	Towing	1400kg (braked)
Driveline		Performance	
Driven wheels	FWD	Max. speed (km/h)	211 (210)
	Brakes	0-100 km/h (sec)	8.5 (8.8)
Front 304mm x 28mm ventilated disc		Fuel consumption (L/100 km)*	
Rear	268mm x 12mm solid disc	Combined	8.8
	ABS	Urban	5.2
	Electronic Brake-force Distribution	Extra urban	6.5
	Brake Assist	CO ₂ emissions (g/km)*	
Additional features	Active Traction Control	Combined	150g/km
	Hill Hold	*Fuel consumption will vary depending on driving conditions/style, vehicle conditions and options/accessories. Source of fuel consumption date ADR81/02 combined cycle. Figures quoted for 17" tyre package.	
	Electronically Controlled Brake system		
	Brake hold		