

# Technical Data – Audi A4 2.0 TFSI quattro S tronic (185 kW)

Program for Australia

Status: February 2016

<b>Engine / electronics</b>	
Engine type	Inline 4-cylinder spark-ignition engine with gasoline direct injection, exhaust turbocharger and Audi valvelift system
Valve gear / number of valves per cylinder	Roller cam followers, continuous intake and exhaust camshaft adjustment, exhaust valve stroke adjustment AVS / 4
Displacement in cc / bore x stroke in mm / compression	1984 / 82.5 x 92.8 / 9.6
Max. power output in kW / at rpm	185 / 5000 - 6000
Max. torque in Nm / at rpm	370 / 1600 - 4500
Mixture preparation	Sequential high-pressure direct and multipoint manifold injection with adaptive idle-charge control, overrun fuel cut-off, adaptive lambda control; mapped ignition with solid-state high-voltage distribution via single-spark coils, cylinder-selective adaptive knock control; manifold pressure measurement, active boost-pressure control via an electric wastegate actuator
Exhaust emission control	Close-coupled ceramic catalytic converter, oxygen sensor in front of turbocharger and behind catalytic converter
Emissions class	EU 6
Alternator in A / battery in A/Ah	110 - 150 / 340/58
Start-stop system	Switches the engine off if the vehicle is stationary and the brake is engaged.
<b>Drivetrain / transmission</b>	
Drive type	quattro permanent all-wheel drive with self-locking center differential and torque vectoring
Clutch	Hydraulically operated wet dual clutch axially arranged, dual-mass flywheel with centrifugal pendulum
Transmission type	7-speed S dual-clutch transmission
Gear ratio in 1st gear / 2nd gear	3.188 / 2.190
Gear ratio in 3rd gear / 4th gear	1.517 / 1.057
Gear ratio in 5th gear / 6th gear	0.738 / 0.557
Gear ratio in 7th gear / 8th gear	0.433 / -
Reverse gear / final drive ratio	2.750 / 4.270
<b>Suspension / steering / brakes</b>	
Front suspension	Independent-wheel suspension, five-link axle with front track rod, aluminum transverse link, subframe and tubular anti-roll bar
Rear suspension	Independent-wheel suspension, five-link axle with rear track rod, resiliently mounted subframe and anti-roll bar
Steering / steering ratio / turning circle in m	Electromechanical steering with speed-dependent power assistance / 15.9 / 11.6
Brake system	Dual circuit brake system split between axles (black/white brake circuit split), antilock brake system ABS with electronic brake-force distribution EBD, electronic differential lock EDL, traction control ASR, electronic stabilization control ESC
Wheels / tires	19 inch alloy wheels with 245/35 R19 tires
<b>Performance / consumption / acoustics</b>	
Top speed in km/h	250
Acceleration, 0-100 km/h in s	5.8
Fuel / octane value	Premium sulfur-free according to EN 228 / E25 95 RON / 95 RON
Idling / drive-past exterior noise level in dB	71 / 72
<b>Consumption / emissions</b>	
<b>19 inch alloy wheels</b>	245/35 R19 93Y, HZ1
Fuel consumption: city / highway / combined, in l/100 km	7.9 / 5.4 / 6.3
CO <sub>2</sub> mass emission city / highway / combined, in g/km	178 / 123 / 144
<b>Servicing / Warranty</b>	
Scheduled service intervals	15,000km or 12 months, whichever come first
Vehicle / paint / rust perforation warranty	unlimited kilometres up to 3 years / 3 years / 12 years
<b>Weights / loads</b>	
Unladen weight according to EU (excluding driver) / (including driver) / gross weight limit in kg	1510 / 1585 / 2080
Axle load limit at front / rear in kg	1075 / 1120
Trailer load limit on 8% / 12% gradient, braked / unbraked in kg	1900 / 1700 / 750
Roof load limit / permissible nose weight in kg	90 / 80
<b>Capacities</b>	
Cooling system capacity (incl. heating) in l	7.8
Engine oil capacity (including filter) in l	5.2
Fuel tank capacity in l	58
<b>Body / dimensions</b>	
Body type / number of doors / seats	Galvanized, unitary steel body, crumple zones at front and rear / 4 doors with additional side protection / 5
Drag coefficient Cd / frontal area A in m <sup>2</sup> (sq ft)	0.27 / 2.20
Length / width excluding mirrors / height in mm	4726 / 1842 / 1427
Wheelbase / track at front/rear in mm	2820 / 1572 / 1555
Height of loading lip in mm	684
Luggage capacity / with rear seat bench folded in l	480 / 965