| Technical Data | Audi RS 7 Sportback 4.0 TFSI quattro tiptronic (441 kW) |
|---|--|
| Programme for Australia | |
| Engine / electrics | |
| Engine type | V8 engine |
| Valve gear / number of valves per cylinder | Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder |
| Displacement in cc / bore x stroke in mm / compression | 3996 / 86.0 x 86.0 / 10.0 |
| Max. power output in kW (PS) / rpm | 441 / 6000 - 6250 |
| Max. torque in Nm (Ib-ft) / at rpm | 800/ 2050 - 4500 |
| Mixture preparation | Direct injection |
| Exhaust emission control | Catalytic converter, oxygen sensor, gasoline particulate filter |
| Emissions standard | 2020 |
| Start-stop / REM | yes / yes |
| Battery in A / Ah | 380 / 68 |
| Max. electrical output at 12V in kilowatts | 3 |
| On-board voltage 1 in volts | 12 |
| On-board voltage 2 in volts | 48 |
| Drivetrain / transmission | |
| Drive type | quattro permanent all-wheel drive with self-locking center differential |
| Type of center differential | Self-locking Self-locking |
| Type of rear axle differential | Standard |
| Clutch | Hydraulic torque converter with lock-up clutch |
| Transmission type | 8-speed tiptronic |
| Transmission ratio in 1st/2nd gear | 4.714 / 3.143 |
| Transmission ratio in 3rd/4th gear | 2.106 / 1.667 |
| Transmission ratio in 5th/6th gear | 1.285 / 1.000 |
| Transmission ratio in 7th/8th gear | 0.839 / 0.667 |
| Reverse gear ratio / final drive ratio 1-2 | 3.317 / 3.204 |
| Suspension / steering / brakes | |
| Type and design of front-axle suspension | Five-link front suspension; tubular anti-roll bar |
| Type and design of rear-axle suspension | Five-link rear suspension; tubular anti-roll bar |
| Steering | Electromechanical steering with speed-dependent power assistance |
| Steering ratio min. / max. | - / 15.8 Dual-circuit brake system with black/white split for front/rear axles; |
| Brake control system | ESC/ABS/EBD; brake booster, hydraulic brake assist |
| Basic tires, front axle | 285/30 R22 |
| Basic tires, rear axle | 285/30 R22 |
| Wheels, front axle | Cast aluminum 10.5Jx22" |
| Wheels, rear axle | Cast aluminum 10.5Jx22" |
| Performance / consumption / acoustics | |
| Top speed in km/h | 280 |
| Limited | yes |
| Acceleration, 0-100 km/h | 3.6 |
| Fuel type / octane value | Gasoline / 98 |
| Fuel standard Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per | DIN EN 228 |
| ECE R51 03 in db (A) | 88.5 / - / 71 |
| Consumption / emissions* | 16.3 / 8.9 / 11.6 |
| Fuel consumption: urban / extra urban / combined, in I/100 km CO ₂ mass emission, combined, in g/km | |
| Weights / loads | 265 |
| | 2065 / 2140 / 2725 |
| Unladen weight without driver / with driver / gross weight limit in kg Gross weight limit min. / max. in kg | 2065 / 2140 / 2735 2735 / 2735 |
| Front/rear axle load limit in kg | 1390 / 1400 |
| Rear axle load limit in kg | 1400 / 1400 |
| Roof load limit / permissible nose weight in kg | 100 / 95 |
| | 100 / 00 |
| | |
| Capacities | 12.1 |
| Capacities Cooling system capacity (incl. heating) in liters | 12.1 11 |
| Capacities Cooling system capacity (incl. heating) in liters Engine oil capacity, including filter (change volume) in liters | 11 |
| Capacities Cooling system capacity (incl. heating) in liters Engine oil capacity, including filter (change volume) in liters Fuel tank capacity in liters | |
| Capacities Cooling system capacity (incl. heating) in liters Engine oil capacity, including filter (change volume) in liters Fuel tank capacity in liters Dimensions / body | 11 73 |
| Capacities Cooling system capacity (incl. heating) in liters Engine oil capacity, including filter (change volume) in liters Fuel tank capacity in liters Dimensions / body Body type / number of doors | 11 |
| Capacities Cooling system capacity (incl. heating) in liters Engine oil capacity, including filter (change volume) in liters Fuel tank capacity in liters Dimensions / body Body type / number of doors Drag coefficient Cd / frontal area A in m² Standard dimensions (length / width excluding mirrors / height with steel springs / height | 11 73 Unitary steel/aluminum composite construction / 5 0.32 / 2.35 |
| Capacities Cooling system capacity (incl. heating) in liters Engine oil capacity, including filter (change volume) in liters Fuel tank capacity in liters Dimensions / body Body type / number of doors Drag coefficient Cd / frontal area A in m ² | 11 73 Unitary steel/aluminum composite construction / 5 0.32 / 2.35 |
| Capacities Cooling system capacity (incl. heating) in liters Engine oil capacity, including filter (change volume) in liters Fuel tank capacity in liters Dimensions / body Body type / number of doors Drag coefficient Cd / frontal area A in m² Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm Width including mirrors in mm | 11 73 Unitary steel/aluminum composite construction / 5 0.32 / 2.35 5009 / 1950 / 1424 / 1424 |
| Capacities Cooling system capacity (incl. heating) in liters Engine oil capacity, including filter (change volume) in liters Fuel tank capacity in liters Dimensions / body Body type / number of doors Drag coefficient Cd / frontal area A in m² Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm | 11 73 Unitary steel/aluminum composite construction / 5 0.32 / 2.35 5009 / 1950 / 1424 / 1424 2118 |
| Capacities Cooling system capacity (incl. heating) in liters Engine oil capacity, including filter (change volume) in liters Fuel tank capacity in liters Dimensions / body Body type / number of doors Drag coefficient Cd / frontal area A in m² Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm Width including mirrors in mm Wheelbase / track width front/rear in mm | 11 73 Unitary steel/aluminum composite construction / 5 0.32 / 2.35 5009 / 1950 / 1424 / 1424 2118 2930 / 1668 / 1650 |
| Capacities Cooling system capacity (incl. heating) in liters Engine oil capacity, including filter (change volume) in liters Fuel tank capacity in liters Dimensions / body Body type / number of doors Drag coefficient Cd / frontal area A in m² Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm Width including mirrors in mm Wheelbase / track width front/rear in mm Overhang angle of steel springs, front/rear in degrees | 11 73 Unitary steel/aluminum composite construction / 5 0.32 / 2.35 5009 / 1950 / 1424 / 1424 2118 2930 / 1668 / 1650 13.20 / 12.50 |
| Capacities Cooling system capacity (incl. heating) in liters Engine oil capacity, including filter (change volume) in liters Fuel tank capacity in liters Dimensions / body Body type / number of doors Drag coefficient Cd / frontal area A in m² Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm Width including mirrors in mm Wheelbase / track width front/rear in mm Overhang angle of steel springs, front/rear in degrees Overhang angle of air spring front/rear in degrees | 11 73 Unitary steel/aluminum composite construction / 5 0.32 / 2.35 5009 / 1950 / 1424 / 1424 2118 2930 / 1668 / 1650 13.20 / 12.50 12.4 / 16.3 |

^{*} Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used