

<b>Technical Data</b>	<b>Audi e-tron 55 quattro (265 kW)</b>
<b>Program for Australia</b>	Status: 01/06/2020
<b>Engine / electrics</b>	
Peak electrical output in kW	300
Continuous electrical output in kW	100
Peak electrical output boost in kW	300
Electrical torque output in Nm	561
Electrical torque output boost in Nm	664
Battery type	Lithium-ion
Battery energy content in kWh	95
Start-stop / REM	no / yes
Max. electrical output at 12V in kilowatts	3
On-board voltage in volts	12
Emissions standard	-
<b>Drivetrain / transmission</b>	
Drive type	All-wheel drive
Transmission type	Two-stage planetary gearbox with single gear
Transmission ratio, front	9,205
Transmission ratio, rear	9,083
Reverse gear ratio / final drive ratio 1-2	Not available / 9.205
<b>Suspension / steering / brakes</b>	
Type and design of front-axle suspension	Five-link front axle; tubular anti-roll bar; air spring suspension
Type and design of rear-axle suspension	Five-link rear axle; tubular anti-roll bar; air spring suspension
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	15.9
Turning circle in m	12.2
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Tires (basic)	255/50 R 20
Wheels (basic)	Cast aluminum flow forming 9.0J x 20"
<b>Performance / acoustics</b>	
Top speed in km/h	200
Limited	yes
Electrical acceleration, 0-100 km/h in s	6.6
Electrical acceleration boost, 0-100 km/h in s	5.7
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	- / - / 68
<b>Consumption / range</b>	
Combined electric power consumption in kWh/100 km*	26.4 – 22.4 (WLTP)
CO <sub>2</sub> emissions combined in g/km	0
Electric range refers to the electric power consumption in the combined WLTP test cycle in km*	up to 436

<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg	2490 / 2565 / 3130
Front / rear axle load limit in kg	1515 / 1740
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg	1800 / 1800 / 750
Roof load limit / permissible nose weight in kg	75 / 80
<b>Capacities</b>	
Cooling system capacity (incl. heating) in l	19.6
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel/aluminum composite construction / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup>	0.28 (with standard exterior mirrors); 0.27 (with virtual exterior mirrors) / 2.65
Standard dimensions (length / width excluding mirrors / height with air springs) in mm	4901 / 1935 / 1629 (with roof-mounted aerial), 1616 (without roof-mounted aerial)
Width including mirrors in mm	2192
Wheelbase // track width front / rear in mm	2928 / 1655 / 1652
Overhang angle front / rear in degrees	15.3 / 21.5
Ramp angle in degrees	13.8
Ground clearance in mm	172
Fording depth in mm	300
Gradeability in %	50
Gradeability in degrees (gradient angle)	27
Height of loading edge in mm	800
Luggage capacity behind 2nd seat bench, open / closed in l	660 / not available
Largest luggage compartment capacity - behind the 1st seat row in l	1725

\* Figures depending on the chosen equipment level