

Technical Data

Audi e-tron Sportback 55 quattro

Program for Australia

Status: 01/06/2020

Engine / electrics

Peak electrical output in kW	300
Continuous electrical output in kW	100
Peak electrical output boost in kW	300
Electrical torque output in Nm	561
Electrical torque output boost in Nm	664
Battery type	Lithium-ion
Battery energy content in kWh	95
Battery in A / Ah	380 / 68
Max. electrical output at 12V in kilowatts	3
On-board voltage 1 in volts	12
On-board voltage 3 in volts	400
Start-stop / REM	no / yes
Emissions standard	-

Drivetrain / transmission

Drive type	quattro permanent all-wheel drive
Transmission type	single-speed
Transmission ratio in 1st/2nd gear	9.205 / not available
Reverse gear ratio / final drive ratio 1-2	Not available / 9.205

Suspension / steering / brakes

Type and design of front-axle suspension	Five-link front axle; tubular anti-roll bar; air spring suspension
Type and design of rear-axle suspension	Five-link rear axle; tubular anti-roll bar; air spring suspension
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	15.9
Turning circle	12.2
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Basic tires, front axle	265/45 R 21
Basic tires, rear axle	265/45 R 21
Wheels, front axle	Cast aluminum flow forming 9.5Jx21"
Wheels, rear axle	Cast aluminum flow forming 9.5Jx21"

Performance / acoustics

Top speed in km/h	200
Limited	yes
Electrical acceleration, 0-100 km/h in seconds	5.7
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	- / - / 68

Consumption / range

Electric power consumption, combined, in kWh/100 km *	26.0-21.9 (WLTP)
CO ₂ emissions, combined, in g/km	0
Electrical range based on current consumption in combined WLTP driving cycle in km*	up to 446

Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg	2480 / 2555 / 3150
Front/rear axle load limit in kg	1530 / 1760
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg	1800 / 1800 / 750
Roof load limit / permissible nose weight in kg	75 / 80
Capacities	
Cooling system capacity (incl. heating) in liters	19.6
Dimensions / body	
Body type / number of doors	Unitary steel/aluminum composite construction / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m ²	0.25 / 2.65
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm	4901 / 1935 / not available / 1616
Width including mirrors in mm	2189
Wheelbase / track width front/rear in mm	2928 / 1655 / 1655
Overhang angle of air spring front/rear in degrees	15.3 / 21.5
Height of loading edge with steel springs / air springs in mm	Not available / 801
Luggage capacity behind 2nd seat bench, open / closed in l	615 / not available
Largest luggage compartment capacity - behind the 1st seat row in l	1665
Open luggage compartment - behind the 2nd seat row in l	615

* Figures depend on the equipment selected