

Technical Data		Audi Q2 35 TFSI S tronic (110 kW)	
Program for Australia		Status: 16/04/2020	
Engine / electrics			
Engine type		Inline 4-cylinder engine	
Valve gear / number of valves per cylinder		Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder	
Displacement in cc / bore x stroke in mm / compression		1498 / 74.5 x 85.9 / 10.5	
Max. power output in kW / at rpm		110 / 5000 - 6000	
Max. torque in Nm / at rpm		250 / 1500 - 3500	
Mixture preparation		Direct injection, lambda control, knock control, turbocharger, intercooler	
Exhaust emission control		Catalytic converter, oxygen sensor	
Emissions standard		EU6	
Start-stop / REM		yes / yes	
Battery in A / Ah		320 / 59	
Max. electrical output at 12V in kilowatts		1.3	
Drivetrain / transmission			
Drive type		Front-wheel drive	
Clutch		2 hydraulically actuated dry clutches, asbestos/lead-free linings, dual-mass flywheel	
Transmission type		7-speed S tronic	
Transmission ratio in 1st/2nd gear		3.500 / 2.087	
Transmission ratio in 3rd/4th gear		1.343 / 0.933	
Transmission ratio in 5th/6th gear		0.974 / 0.778	
Transmission ratio in 7th/8th gear		0.653 / -	
Reverse gear ratio / final drive ratio 1-2		3.722 / 4.800	
Suspension / steering / brakes			
Type and design of front-axle suspension		McPherson struts, front	
Type and design of rear-axle suspension		Compound link rear suspension	
Steering		Electromechanical steering with speed-dependent power assistance	
Steering Ratio		14.1	
Turning circle / turning circle optional in m		11.1 / -	
Brake control system		Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist	
Tires (basic)		215/50 R 18	
Wheels (basic)		Alloy 7.0Jx18"	
Performance / acoustics			
Top speed in km/h		218	
Acceleration, 0-100 km/h		8.6	
Fuel type / octane value		Gasoline / 95	
Fuel standard		DIN EN 228	
Exterior noise level when stationary / drive-past as per ECE R51.03 in db (A)		78.9 / 66	

Consumption / emissions*	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers	6.0 / 4.7 / 5.2
CO ₂ emissions combined in grams per kilometer	119
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg	1305 / 1380 / 1870
Front/rear axle load limit in kg	1000 / 945
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg	1700 / 1500 // 690
Roof load limit / permissible nose weight in kg	60 / 75
Capacities	
Cooling system capacity (incl. heating) in liters	11.2
Engine oil capacity, including filter (change volume) in liters	4.3
Fuel tank capacity in liters	50
Dimensions / body	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m ²	0.31 / 2.29
Standard dimensions (length / width excluding mirrors / height with steel springs) in mm	4208 / 1794 / 1537
Width including mirrors in mm	2009
Wheelbase / track width front/rear in mm	2601 / 1546 / 1542
Height of loading edge with steel springs in mm	740
Luggage capacity behind 2nd seat bench, open in l	405
Largest luggage compartment capacity - behind the 1st seat row in l	1050
Open luggage compartment - behind the 2nd seat row in l	405

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used