

<b>Technical Data</b>	<b>A8 55 TFSI 3.0 quattro tiptronic (250 kW)</b>
Program for Australia	Status: July 2018
<b>Engine / electronics</b>	
Engine type	V6 engine
Valve gear / number of valves per cylinder	Roller cam followers, continual inlet/exhaust camshaft adjustment, hydraulic valve play adjustment / 2/2 inlet/exhaust valves per cylinder
Displacement in cm <sup>3</sup> / bore x stroke in mm / compression	2995 / 84.5 x 89.0 / 11.2
Max. power output in kW / at rpm	250 / 5000 - 6400
Max. torque in Nm / at rpm	500 / 1370 - 4500
Mixture preparation	Direct injection, Lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Close-coupled catalytic converter, oxygen sensor
Emission class	EU6
Alternator in A / battery rated capacity in Ah	- / 70
Max. electrical output at 12V in kilowatts	3
Start/Stop / REM	yes / yes
On-board voltage 1 in volts	12
On-board voltage 2 in volts	48
<b>Drivetrain / transmission</b>	
Drive type	quattro all-wheel drive
Type of centre differential	Self-locking
Type of rear axle differential	Standard
Clutch	Hydraulic torque converter with lock-up clutch
Transmission type	8-speed tiptronic / automatic
Transmission ratio in 1st/2nd gear	4.714 / 3.143
Transmission ratio in 3rd/4th gear	2.106 / 1.667
Transmission ratio in 5th/6th gear	1.285 / 1.000
Transmission ratio in 7th/8th gear	0.839 / 0.667
Reverse gear transmission ratio / final drive ratio 1-2	3.317 / 3.076
<b>Suspension / steering / brakes</b>	
Front suspension	Five-link front axle; tubular anti-roll bar; air spring suspension
Rear suspension	Five-link rear axle; tubular anti-roll bar; air spring suspension
Steering / steering ratio / turning circle in m	Electromechanical steering with speed-dependent power assistance / 15.8 / 12.5
Brake control system	Dual-circuit brake system with black/white split for front/rear axles; ESC/ABS/EBD; brake booster, hydraulic brake assist
Wheels / tyres	Cast aluminium 9.0J x 19 / 255/45 R19
<b>Performance / consumption / acoustics</b>	
Top speed in km/h	250
Governed	yes
Acceleration, 0-100 km/h	5.6
Fuel type / octane value	Unleaded / 95 RON
Fuel standard	Premium sulfur-free according to DIN EN 228
Idling / drive-past exterior noise level in dB (A)	71.5 / 66
<b>Fuel consumption / emissions</b>	

Tyre package 19"	255/45 R19 104Y, Q55
Fuel consumption, urban/extra-urban/combined in litres per 100 kilometres	10.8 / 6.6 / 8.2
CO <sub>2</sub> emissions urban/extra-urban/combined in grams per kilometre	246 / 151 / 186
Tyre package 20"	265/40 R20 104Y, Q57
Fuel consumption, urban/extra-urban/combined in litres per 100 kilometres	10.9 / 6.8 / 8.3
CO <sub>2</sub> emissions urban/extra-urban/combined in grams per kilometre	247 / 154 / 188
<b>Servicing / guarantee</b>	
Service interval	According to service indicator, depending on driving style and operating conditions between 15,000 km or 1 year
Vehicle / paint / rust perforation guarantee	3 years with unlimited mileage / 3 years / 12 years
<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg	1920 / 1995 / 2680
Front/rear axle load limit in kg	1345 / 1435
Trailer load limit on 8% / 12% gradient, braked / unbraked in kg	2300 / 2300 / 750
Roof load limit / permissible nose weight in kg	100 / 95
<b>Capacities</b>	
Cooling system capacity (incl. heating) in l	11
Engine oil capacity, including filter (change volume) in litres	7.6
Fuel tank capacity in litres	72
Optional fuel tank capacity in litres	82
<b>Body / dimensions</b>	
Body type / number of doors / number of seats	Audi Space Frame (ASF) / 4 / 5
Drag coefficient Cd / frontal area A in m <sup>2</sup>	0.27 / 2.43
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm	5172 / 1945 / - / 1473
Width including mirrors in mm	2130
Wheelbase / track width front/rear in mm	2998 / 1644 / 1633
Overhang angle of air spring front/rear in degrees	14.0 / 13.7
Height of loading edge with steel springs / air springs in mm	- / 697
Luggage capacity behind 2nd seat bench, open / closed in l	- / 505