

Technical Data	Audi RS Q3 (294 kW)
Program for Australia	
Engine / electrics	
Engine type	Inline 5-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	2480 / 82.5 x 92.8 / 10.0
Max. power output in kW / rpm	294 / 5850 - 7000
Max. torque in Nm / at rpm	480 / 1950 - 5850
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter
Emissions standard	EU6
Start-stop / REM	yes / no
Battery in A / Ah	420 / 75
Max. electrical output at 12V in kilowatts	2.1
On-board voltage 1 in volts	12
On-board voltage 2 in volts	-
Drivetrain / transmission	
Drive type	quattro permanent all-wheel drive with electronically controlled multi-plate clutch
Clutch	Dual clutch
Transmission type	7-speed S tronic
Transmission ratio in 1st/2nd gear	3.563 / 2.526
Transmission ratio in 3rd/4th gear	1.679 / 1.022
Transmission ratio in 5th/6th gear	0.788 / 0.761
Transmission ratio in 7th/8th gear	0.635 / -
Reverse gear ratio / final drive ratio 1-2	2.789 / 4.375
Suspension / steering / brakes	
Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	Four-link rear suspension
Steering	Electromechanical progressive steering with speed-dependent power assistance
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Tyres (basic)	255/35 R21 (extra load)
Wheels (basic)	Cast aluminum flow forming 8.5Jx21"
Performance / acoustics	
Top speed in km/h	250
Limited	yes
Acceleration, 0-100 km/h (0-62.1 mph)	4.5
Fuel type / octane value	Petrol / 98
Fuel standard	DIN EN 228 (Petrol)
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in dB (A)	88.0 / - / 71

Consumption / emissions*	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers	11.4 / 7.4 / 8.9
CO₂ emissions combined in grams per kilometer	203
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg	1715 / 1790 / 2250
Front/rear axle load limit in kg	1140 / 1195
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg	1900 / 1900 // 750
Roof load limit / permissible nose weight in kg	75 / 90
Capacities	
Cooling system capacity (incl. heating) in liters	9.6
Engine oil capacity, including filter (change volume) in liters	7.1
Fuel tank capacity in liters	63
Dimensions / body	
Body type / number of doors	- / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m²	0.35 / 2.46
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm	4506 / 1851 / 1602 / not available
Width including mirrors in mm	2024
Wheelbase / track width front/rear in mm	2681 / 1590 / 1583
Overhang angle of steel springs, front / rear in degrees	19.00 / 15.20
Luggage capacity behind 2nd seat bench, open / closed in l	530 / -
Largest luggage compartment capacity - behind the 1st seat row in l	1525
Open luggage compartment - behind the 2nd seat row in l	530