

Technical Data	Audi RS Q3 Sportback (294 kW)
Program for Australia	
Engine / electrics	
Engine type	Inline 5-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	2480 / 82.5 x 92.8 / 10.0
Max. power output in kW / rpm	294 / 5850 - 7000
Max. torque in Nm / at rpm	480 / 1950 - 5850
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor, petrol particulate filter
Emissions standard	EU6
Start-stop / REM	yes / no
Battery in A / Ah	420 / 75
Max. electrical output at 12V in kilowatts	2.1
On-board voltage 1 in volts	12
On-board voltage 2 in volts	-
Drivetrain / transmission	
Drive type	quattro permanent all-wheel drive with electronically controlled multi-plate clutch
Clutch	Dual clutch
Transmission type	7-speed S tronic
Transmission ratio in 1st/2nd gear	3.563 / 2.526
Transmission ratio in 3rd/4th gear	1.679 / 1.022
Transmission ratio in 5th/6th gear	0.788 / 0.761
Transmission ratio in 7th/8th gear	0.635 / -
Reverse gear ratio / final drive ratio 1-2	2.789 / 4.375
Suspension / steering / brakes	
Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	Four-link rear suspension
Steering	Electromechanical progressive steering with speed-dependent power assistance
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Tyres (basic)	255/35 R21 (extra load)
Wheels (basic)	Cast aluminum flow forming 8.5Jx21"
Performance / acoustics	
Top speed in km/h	250
Limited	yes
Acceleration, 0-100 km/h	4.5
Fuel type / octane value	Gasoline / 98
Fuel standard	DIN EN 228 (petrol)
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in dB (A)	88.0 / - / 71

<b>Consumption / emissions*</b>	
<b>Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers</b>	11.4 / 7.5 / 8.9
<b>CO<sub>2</sub> emissions combined in grams per kilometer</b>	204
<b>Weights / loads</b>	
<b>Unladen weight without driver / with driver / gross weight limit in kg</b>	1700 / 1775 / 2250
<b>Front/rear axle load limit in kg</b>	1140 / 1195
<b>Trailer load limit on 8% / 12% gradient, braked // unbraked in kg</b>	1900 / 1900 // 750
<b>Roof load limit / permissible nose weight in kg</b>	75 / 90
<b>Capacities</b>	
<b>Cooling system capacity (incl. heating) in litres</b>	9.6
<b>Engine oil capacity, including filter (change volume) in litres</b>	7.1
<b>Fuel tank capacity in litres</b>	63
<b>Dimensions / body</b>	
<b>Body type / number of doors</b>	- / 5
<b>Number of seats</b>	5
<b>Drag coefficient Cd / frontal area A in m<sup>2</sup></b>	0.37 / 2.42
<b>Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm</b>	4507 / 1851 / 1557 / not available
<b>Width including mirrors in mm</b>	2024
<b>Wheelbase / track width front/rear in mm</b>	2681 / 1590 / 1583
<b>Overhang angle of steel springs, front / rear in degrees</b>	19.00 / 15.20
<b>Luggage capacity behind 2nd seat bench, open / closed in l</b>	530 / -
<b>Largest luggage compartment capacity - behind the 1st seat row in l</b>	1400
<b>Open luggage compartment - behind the 2nd seat row in l</b>	530