Forester specifications¹

ENGINE TYPE		NATU	JRALLY ASPIRA	ATED	TURBOCHA	RGED PETROL	TURBOCHAF	HARGED DIESEL		
Model Variant	Model Variant		2.0i-L	2.5i-L	2.5i-S	2.0XT	2.0XT Prem	2.0D-L	2.0D-S	
Transmission										
	6-speed manual transmission		•					•	•	
Lineartronic™ CVT with manu	Lineartronic™ CVT with manual mode			•	•	•	•	•	•	
Engine										
Engine type		Horizontally-opposed Boxer 4-cylinder, petrol engine			horizontally-	Direct injection, turbocharged horizontally-opposed Boxer 4-cylinder, petrol engine		Turbocharged horizontally- opposed Boxer 4-cylinder, diesel engine		
Valve mechanism		DOHC with Dual AVCS	DOHC with AVCS		DOHC wit	DOHC with Dual AVCS		HC		
Bore x stroke		mm	84 x 90	94 >	< 90		x 86		x 86	
Capacity		СС	1995	2498			1998		98	
Compression ratio			10.5:1	10):1).6:1	15.2:1		
Fuel tank capacity		litres				60				
Fuel system			Multi point sequential injection			Direct injection		Common rail direct injectio		
Fuel requirement (min) RON		91			95		Diesel			
Performance ²										
Maximum power output (DIN	Maximum power output (DIN) kW/rp		110kW@6200rpm	126kW@	5800rpm	177kW@	177kW@5600rpm		3600rpm	
Maximum torque (DIN)	Maximum torque (DIN) Nm/rpm		198Nm@4200rpm	235Nm@	4100rpm	350Nm@24	100-3600rpm	350Nm@16	00-2400rpm	
Acceleration 0 – 100 km/h		seconds	10.6	9	.9		7.5	9	.9	
Electronic Throttle Control sy	ystem (ETC)		Drive-by-wire							
Fuel consumption (ADR 81/02 For comparison purposes on Real world results may vary ³ :	ly.									
	combined	I/100km	7.2	8			3.5	5.9 (MT) / 6.4 (CVT)		
	urban	I/100km	8.9).2	1	1.2	7.3 (MT) / 7.6 (CVT)		
	extra urban	I/100km	6.4	6.8			7		5.7 (CVT)	
	combined	(g/km)	168	18	37		197	152 (MT) /	166 (CVT)	
Transmission										
Gear ratio		1st	3.818	3.5		3.505		3.454 (MT) / 3.505 (CVT)		
		2nd	1.947	Continuously Variable		Continuously Variable		1.888 (MT) / Continuously Variab		
		3rd	1.296	Continuou			Continuously Variable		tinuously Variable	
		4th	1.029	Continuously Variable		Continuously Variable		0.785 (MT) / Continuously Variab		
		5th	0.825	Continuously Variable		Continuously Variable		0.634 (MT) / Continuously Variab		
(S# = SI-Drive Sport Sharp M	(S# = SI-Drive Sport Sharp Mode) 6th		0.738 Continuously Var		sly Variable	Continuously Variable		0.557 (MT) / Continuously Var		
		7th		n/a		1-	(S#0.785)		(CVT)	
		8th		n/a		, · ·	0.611)		/a	
Gear ratio – reverse			4.072	3.6			.345	3.636 (MT) / 2.345 (CVT)		
Final reduction gear ratio			4.444	3.900		4	4.111		4.444 (MT) / 4.111 (CVT)	

^{1.} Subaru Australia reserves the right to change mechanical specification and equipment levels without notice. 2. All performance data measured using 95RON as required by Australian Design Rule 81/02. Vehicles tested in accordance with ADR 81/02. Acceleration test performed under controlled conditions. 3. Fuel consumption figures quoted are measured in accordance with Australian Design Rule 81/02 and are for comparison purposes only. Real world results may vary based on individual driving circumstances e.g. traffic conditions, driving style, vehicle conditions, fuel quality, climatic conditions etc. Quoted figures may not reflect real world fuel consumption .

Forester specifications¹

ENGINE TYPE		NATU	JRALLY ASPIRA	ATED	TURBOCHA	RGED PETROL	TURBOCHAF	TURBOCHARGED DIESEL			
Model Variant		2.0i-L	2.5i-L	2.5i-S	2.0XT	2.0XT Prem	2.0D-L	2.0D-S			
Symmetrical All-Wheel Drive											
Туре	Centre Differential with Viscous Limited Slip Differential			Centre Differential with a Viscous Limited Slip Differential							
	Auto	n/a	Active Torque Split								
Steering											
Steering		Electric power assistance rack and pinion									
Minimum turning circle	m			•	10.6						
Suspension											
Туре	Front		Ma	cPherson struts,	lower L-arms, co	il springs, stabiliz	er bar				
	Rear		·	Double wishb	one type, indepe	ndent suspension	1				
Brakes											
Туре	Front	Ventilated disc brake Solid disc brake									
	Rear		Solid disc brake			Ventilated disc brake		Ventilated disc brake			
Brake booster type		Tandem									
ABS		4-channel, 4-sensor ABS with Electronic Brakeforce Distribution									
Wheels and Tyres											
Tyre manufacturer		Yoko	Yokohama Bridgestone				Yokohama	Bridgestone			
Tyres (width/profile/size/load index/speed i	rating)	225/60	0 R17 99H 225/55 R18 98H				225/60 R17 99H	225/55 R18 98F			
Rim size		17	17x7J 18x7J				17x7J	18x7J			
Spare wheel		1	7"	18"			17"	18"			
Measurement											
Overall length	mm		4610			595	4610				
Overall width / height	mm				1795 / 1735						
Wheel base	mm				2640						
Front / Rear track	mm				1545 / 1555						
Minimum ground clearance ²	mm				220						
Cargo volume – rear seat up/down	litres		1481		422/1474		422 / 1481	422/1474			
Kerb weight³ (MT / CVT)	kg	1527	1568	1571	1655	1657	1643 / 1698	1677 / 1729			
Tare mass ³	kg	1487	1528	1531	1615	1617	1603 / 1658	1637 / 1689			
Seating capacity				-	5						
Towing											
With / without trailer brakes (max)	kg		1500 / 750				/ 750				
Tow ball down load (max)	kg		150		180						

^{1.} Subaru Australia reserves the right to change mechanical specification and equipment levels without notice. 2. Ground clearance at kerb weight. 3. Vehicle kerb weight and tare mass varies according to the types of optional equipment included.

ENGINE TYPE	NAT	URALLY ASPIR	RATED	TURBOCHARGED PETROL		TURBOCHARGED DIESEL	
Model Variant	2.0i-L	2.5i-L	2.5i-S	2.0XT	2.0XT Prem	2.0D-L	2.0D-S
Safety Rating		'	'				'
5 star ANCAP ² safety rating (maximum 5)	•	•	•	•	•	•	•
Collision Avoidance				`			
Symmetrical All-Wheel Drive (SAWD)	•	•	•	•	•	•	•
Vehicle Dynamics Control system (VDC):	•	•	•	•	•	•	•
Electronic Stability Control (ESC)	•	•	•	•	•	•	•
Anti-lock Braking System (ABS)	•	•	•	•	•	•	•
Electronic Brakeforce Distribution (EBD)	•	•	•	•	•	•	•
Brake Assist	•	•	•	•	•	•	•
Traction Control System (TCS)	•	•	•	•	•	•	•
Active Torque Vectoring System					•		
4-wheel disc brakes	•	•	•	•	•	•	•
Hill Start Assist	•	•	•	•	•	•	•
Rear view reverse camera	•	•	•	•	•	•	•
Collision Protection							
SRS³ airbags – dual front, dual front side, curtain and driver knee airbag	•	•	•	•	•	•	•
Front seat belts with pretensioners and load limiters	•	•	•	•	•	•	•
3 point A/ELR rear seat belts	•	•	•	•	•	•	•
Height adjustable seat belt anchors – driver and front passenger	•	•	•	•	•	•	•
Height and angle adjustable front seat headrests	•	•	•	•	•	•	•
Height adjustable rear seat headrests	•	•	•	•	•	•	•
Rear seat headrests for 3 seating positions	•	•	•	•	•	•	•
Ring-shaped passenger safety cell	•	•	•	•	•	•	•
Seat belt warning lights – all seats	•	•	•	•	•	•	•
Child Safety							
Child seat anchor points (x3)	•	•	•	•	•	•	•
ISOFIX anchor points (x2)	•	•	•	•	•	•	•
Rear door child locks	•	•	•	•	•	•	•

^{1.} Subaru Australia reserves the right to change mechanical specification and equipment levels without notice. 2. The Australasian New Car Assessment Program (ANCAP) gives consumers consistent information on the level of occupant protection provided by vehicles in serious front and side crashes. 3. SRS: Supplemental Restraint System. Effective when used in conjunction with seat belts.

ENGINE TYPE	NAT	URALLY ASPIR	ATED	TURBOCHA	RGED PETROL	TURBOCHARGED DIESEL	
Model Variant	2.0i-L	2.5i-L	2.5i-S	2.0XT	2.0XT Prem	2.0D-L	2.0D-S
Intelligent Driving Dynamics							•
Auto Stop Start	•	•	•				
Subaru Intelligent Drive (SI-Drive)	2 modes	2 modes	2 modes	3 modes	3 modes		
EyeSight® featuring:			•		•		
Adaptive cruise control			•		•		
Lane departure warning			•		•		
Lane sway warning			•		•		
Lead vehicle start alert			•		•		
Pre-collision braking system			•		•		
Pre-collision brake assist			•		•		
Pre-collision throttle management			•		•		
Electronic Throttle Control system (ETC)	•	•	•	•	•	•	•
X-Mode		•	•	•	•	(CVT only)	(CVT only)
Exterior		•	•				
Body coloured mirrors and door handles	•	•	•	•	•	•	•
Bonnet with gas strut	•	•	•	•	•	•	•
Chrome type side skirt garnish				•	•		
Chrome type window sills	•	•	•	•	•	•	•
Door mirrors with indicators	•	•		•		•	
Door mirrors with indicators – heated			•		•		•
Dual tail pipes				•	•		
Electric sunroof			•	•	•		
Engine cover				•	•	•	•
Exterior grade badge				•	•	•	
Front and rear wipers	•	•	•	•	•	•	
Fuel cap – tethered	•	•	•	•	•	•	•
Full size spare alloy wheel	•	•	•	•	•	•	•
Rear door, rear quarter and rear windscreen privacy glass	•	•	•	•	•	•	•
Rear spoiler	•	•	•	•	•	•	•
Roof rails	•	•	•	Silver	Silver	•	•
Shark fin antenna	•	•	•		•	•	
Tail pipe covers	•	•	•	•	•	•	•
17" alloy wheels	•	•				•	
18" alloy wheels			•		•		•

^{1.} Subaru Australia reserves the right to change mechanical specification and equipment levels without notice.

ENGINE TYPE	NAT	URALLY ASPIR	ATED	TURBOCHA	RGED PETROL	L TURBOCHARGED DIESEL		
Model Variant	2.0i-L	2.5i-L	2.5i-S	2.0XT	2.0XT Prem	2.0D-L	2.0D-S	
Lighting - Exterior		'			·		'	
Daytime running lights	Halogen	Halogen	LED	LED	LED	Halogen	LED	
Front fog lights	•	•	•	•	•	•	•	
Headlights – dusk-sensing			•	•	•		•	
Headlights – halogen with auto off	•	•				•		
Headlights – self-levelling LED with auto off			•	•	•		•	
Rear bumper reflector(s)	•	•	•	•	•	•	•	
Rear LED stoplight	•	•	•	•	•	•	•	
Rear LED combination lights	•	•	•	•	•	•	•	
Steering Responsive Headlights (SRH)			•	•	•		•	
Lighting – Interior		•		•				
Cabin and cargo area lights	•	•	•	•	•	•	•	
Illuminated ignition ring	•	•				•		
Map lights (x2)	•	•	•	•	•	•	•	
Air-conditioning	•							
Air-conditioning – dual zone climate control	•	•	•	•	•	•	•	
Anti-dust filter	•	•	•	•	•	•	•	
Front and side demisters	•	•	•	•	•	•	•	
Floor heater ducts for rear passengers	•	•	•	•	•	•	•	
Rear windscreen demister – electric	•	•	•	•	•	•	•	
Security								
Immobiliser security system	•	•	•	•	•	•	•	
DataDotDNA®2 security system	•	•	•	•	•	•	•	
Instrumentation and Controls	•							
Adjustable steering wheel – height and telescopic	•	•	•	•	•	•	•	
Electroluminescent gauges with colour MID	•	•	•	•	•	•	•	
Hazard warning indicators	•					•		
Instrument cluster	•	•	•	•	•	•	•	
Manual mode		•	•	•	•	CVT	CVT	
One touch lane change indicator	•	•				•		
Paddle gear shifters		•	•	•	•	CVT	CVT	
Sports pedals				•	•			
Twin trip meter (switchable)	•		•			•		

 $^{1. \,} Subaru \, Australia \, reserves \, the \, right \, to \, change \, mechanical \, specification \, and \, equipment \, levels \, without \, notice. \, 2. \, DataDotDNA^{\otimes} \, is \, a \, theft \, deterrent \, not \, a \, theft \, prevention \, mechanism.$

ENGINE TYPE	NAT	URALLY ASPIRATED TURBOO			RGED PETROL	TURBOCHARGED DIESEL	
Model Variant	2.0i-L	2.5i-L	2.5i-S	2.0XT	2.0XT Prem	2.0D-L	2.0D-S
Instrumentation and Controls (continued)		1			1		
Steering wheel controls:	•	•	•	•	•	•	•
Audio	•	•	•	•	•	•	•
Cruise	•	•	•	•	•	•	•
Bluetooth®2	•	•	•	•	•	•	•
EyeSight [®]			•		•		
MID	•	•	•	•	•	•	•
SI-Drive	•	•	•	•	•		
Multi-Information Display unit (MID) featuring:	•	•	•	•	•	•	•
3.5" LCD screen	•	•	•	•	•	•	•
Journey information	•	•	•	•	•	•	•
EyeSight® display			•		•		
Auto Stop Start	•	•	•				
SI-Drive display	•	•	•	•	•		
Warning display	•	•	•	•	•	•	•
X-Mode display		•	•	•	•	CVT	CVT
Digital speedometer	•	•	•	•	•	•	•
Multi-Function Display unit (MFD) featuring:	•	•	•	•	•	•	•
4.3" LCD screen	•	•	•	•	•	•	•
Outside temperature and clock	•	•	•	•	•	•	•
Fuel economy and journey information	•	•	•	•	•	•	•
Air-conditioning and seat belt display	•	•	•	•	•	•	•
Eco-gauge information	•	•	•	•	•	•	•
EyeSight® display			•		•		
Turbo boost pressure display				•	•		
VDC operating information	•	•	•	•	•	•	•
Vehicle condition / maintenance self-check	•	•	•	•	•	•	•
Warning display	•	•	•	•	•	•	•
X-Mode display		•	•	•	•	CVT	CVT
Storage							
Cargo hooks	•	•	•	•	•	•	•
Centre console box – sliding armrest		•	•	•	•	CVT	CVT
Cupholders – centre console	•	•	•	•	•	•	•
Cupholders – rear	•	•	•	•	•	•	•
Door pockets with integrated bottle holder – front and rear	•	•	•		•	•	•

^{1.} Subaru Australia reserves the right to change mechanical specification and equipment levels without notice. 2. Bluetooth® is a registered trademark of Bluetooth SIG Inc. System operation ability is subject to the Bluetooth® wireless technology specification of individual's phone.