

<b>Technical Data</b>		<b>Audi A4 Avant 45 TFSI quattro</b>
<b>Program for Australia</b>		
<b>Engine / electrics</b>		
Engine type	Inline 4-cylinder engine	
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment / 2/2 inlet/exhaust valves per cylinder	
Displacement in cc / bore x stroke in mm / compression	1984 / 82.5 x 92.8 / 9.6	
Max. power output in kW / rpm	183 / 5,000 - 6,500	
Max. torque in Nm / at rpm	370 / 1600 - 4500	
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler	
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter	
Emissions standard	EU6	
Start-stop / REM	yes / yes	
Battery in A / Ah	340 / 58	
Max. electrical output at 12V in kilowatts	3.1	
On-board voltage 1 in volts	12	
<b>Drivetrain / transmission</b>		
Drive type	quattro all-wheel drive with ultra technology	
Type of center differential	Electronically controlled multi-plate clutch	
Type of rear axle differential	quattro ultra	
Clutch	Dual clutch	
Transmission type	7-speed S tronic / dual clutch	
Transmission ratio in 1st/2nd gear	3.188 / 2.190	
Transmission ratio in 3rd/4th gear	1.517 / 1.057	
Transmission ratio in 5th/6th gear	0.738 / 0.557	
Transmission ratio in 7th/8th gear	0.433 / -	
Reverse gear ratio / final drive ratio 1-2	2.750 / 4.410	
<b>Suspension / steering / brakes</b>		
Type and design of front-axle suspension	Five-link front suspension; tubular anti-roll bar	
Type and design of rear-axle suspension	Five-link rear suspension; tubular anti-roll bar	
Steering	Electromechanical steering with speed-dependent power assistance	
Steering ratio	15.9	
Turning circle in m	11.6	
Brake control system	Dual-circuit brake system with black/white split for front/rear axles; ESC/ABS/EBD; brake booster, hydraulic brake assist	
Tyres	245/35 R 19 93 Y	
Wheels	Alloy 8.5Jx19"	
<b>Performance / acoustics</b>		
Top speed in km/h	250	
Limited	yes	
Acceleration, 0-100 km/h	6.0	
Fuel type / octane value	Gasoline / 95	
Fuel standard	DIN EN 228 not available	
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in dB (A)	71.9 / - / 66	

<b>Consumption / emissions</b>	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometere	9.1 / 6.3 / 7.3
CO <sub>2</sub> emissions combined in grams per kilometre	167
<b>Servicing / guarantee</b>	
Service interval	15,000 km / 1 year, whichever comes first
Vehicle / paint / rust perforation guarantee	3 / 3 / 12 (years)
<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg	1590 / 1665 / 2175
Front/rear axle load limit in kg	1085 / 1200
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg	1900 / 1700 // 750
Roof load limit / permissible nose weight in kg	90 / 80
<b>Capacities</b>	
Cooling system capacity (incl. heating) in litres	8.4
Engine oil capacity, including filter (change volume) in litres	5.2
Fuel tank capacity in litres	58
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel/aluminum composite construction / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup>	0.29 / 2.20
Standard dimensions (length / width excluding mirrors / height in mm	4762 / 1847 / 1435
Width including mirrors in mm	2022
Wheelbase / track width front/rear in mm	2820 / 1572 / 1555
Overhang angle of steel springs, front/rear in degrees	12.50 / 15.30
Height of loading edge in mm	630
Luggage capacity in l (2nd row up / 2nd row down)	495 / 1495

\* Fuel consumption and CO<sub>2</sub> emission figures given in ranges depend on the tyres/wheels used