

Technical Data		Audi A4 allroad 40 TDI quattro
Program for Australia		
Engine / electrics		
Engine type	Inline 4-cylinder diesel engine	
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment / 2/2 inlet/exhaust valves per cylinder	
Displacement in cc / bore x stroke in mm / compression	1968 / 81.0 x 95.5 / 15.5	
Max. power output in kW / rpm	140 / 3800 - 4200	
Max. torque in Nm / at rpm	400 / 1750 - 3000	
Mixture preparation	Common rail direct injection	
Exhaust emission control	Oxidation catalyst, water-cooled exhaust gas recirculation, diesel particulate filter	
Emissions standard	EU6	
Start-stop / REM	yes / yes	
Battery in A / Ah	520 / 92	
Drivetrain / transmission		
Drive type	quattro all-wheel drive	
Type of center differential	Electronically controlled multi-plate clutch	
Type of rear axle differential	quattro	
Clutch	Dual clutch	
Transmission type	7-speed S tronic / dual clutch	
Transmission ratio in 1st/2nd gear	3.692 / 2.150	
Transmission ratio in 3rd/4th gear	1.344 / 0.947	
Transmission ratio in 5th/6th gear	0.739 / 0.574	
Transmission ratio in 7th/8th gear	0.462	
Reverse gear ratio / final drive ratio 1-2	2.944 / 4.093	
Suspension / steering / brakes		
Type and design of front-axle suspension	Five-link front suspension; tubular anti-roll bar	
Type and design of rear-axle suspension	Five-link rear suspension; tubular anti-roll bar	
Steering	Electromechanical steering with speed-dependent power assistance	
Steering ratio	15.9	
Turning circle in m	11.6	
Brake control system	Dual-circuit brake system with black/white split for front/rear axles; ESC/ABS/EBD; brake booster, hydraulic brake assist	
Tyres	245/45 R 18	
Wheels	Alloy 7.5Jx18"	
Performance / acoustics		
Top speed in km/h	215	
Limited	yes	
Acceleration, 0-100 km/h	7.8	
Fuel type / octane value	Diesel	

Consumption / emissions	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometere	5.7 / 4.9 / 5.2
CO ₂ emissions combined in grams per kilometre	136
Servicing / guarantee	
Service interval	15,000 km / 1 year, whichever comes first
Vehicle / paint / rust perforation guarantee	3 / 3 / 12 (years)
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg	1645 / 1720 / 2250
Front/rear axle load limit in kg	1085 / 1215
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg	1900 / 1700 // 750
Roof load limit / permissible nose weight in kg	90 / 80
Capacities	
Cooling system capacity (incl. heating) in litres	13.2
Engine oil capacity, including filter (change volume) in litres	5
Fuel tank capacity in litres	61
Dimensions / body	
Body type / number of doors	Unitary steel/aluminum composite construction / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m ²	0.32 / 2.24
Standard dimensions (length / width excluding mirrors / height in mm	4762 / 1847 / 143
Width including mirrors in mm	2022
Wheelbase / track width front/rear in mm	2818 / 1578 / 1566
Height of loading edge in mm	630
Luggage capacity in l (2nd row up / 2nd row down)	495 / 1495

* Fuel consumption and CO₂ emission figures given in ranges depend on the tyres/wheels used