

Technical Data	Audi A5 Coupé 40 TFSI S tronic (140 kW)
<b>Program for Australia</b>	
<b>Engine / electrics</b>	
Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	1984 / 82.5 x 92.8 / 11.7
Max. power output in kW / rpm	140 / 4200 - 6000
Max. torque in Nm / at rpm	320 / 1450 - 4200
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter
Emissions standard	EU 6
Start-stop / REM	yes / yes
Battery in A / Ah	340 / 58
Max. electrical output at 12V in kilowatts	3.1
On-board voltage 1 in volts	12
On-board voltage 2 in volts	-
<b>Drivetrain / transmission</b>	
Drive type	Front-wheel drive
Clutch	Dual clutch
Transmission type	7-speed S tronic
Transmission ratio in 1st/2nd gear	3.188 / 2.190
Transmission ratio in 3rd/4th gear	1.517 / 1.057
Transmission ratio in 5th/6th gear	0.738 / 0.557
Transmission ratio in 7th/8th gear	0.433 / -
Reverse gear ratio / final drive ratio 1-2	2.750 / 4.234
<b>Suspension / steering / brakes</b>	
Type and design of front-axle suspension	Five-link front suspension; tubular anti-roll bar
Type and design of rear-axle suspension	Five-link rear suspension; tubular anti-roll bar
Steering	Electromechanical steering with speed-dependent power assistance
Steering ratio	15.9
Steering ratio	10.0
Turning circle in m	11.5
Brake control system	Dual-circuit brake system with black/white split for front/rear axles; ESC/ABS/EBD; brake booster, hydraulic brake assist
Tyres (basic)	255/35 R19 96 Y
Wheels (basic)	Alloy 8.5Jx19"
<b>Performance / acoustics</b>	
Top speed in km/h	241
Limited	yes
Acceleration, 0-100 km/h	7.3
Fuel type / octane value	Gasoline / 95
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in dB (A)	71.7 / n.a. / 66

<b>Consumption / emissions*</b>	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometres	8.0 / 5.4 / 6.4
CO <sub>2</sub> emissions combined in grams per kilometre	145
<b>Weights / loads</b>	
Unladen weight without driver / with driver / gross weight limit in kg	1455 / 1530 / 1965
Front/rear axle load limit in kg	1050 / 1025
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg	1700 / 1500 // 750
Roof load limit / permissible nose weight in kg	75 / 80
<b>Capacities</b>	
Cooling system capacity (incl. heating) in litres	8.4
Engine oil capacity, including filter (change volume) in litres	5.2
Fuel tank capacity in litres	54
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel/aluminum composite construction / 2
Number of seats	4
Drag coefficient Cd / frontal area A in m <sup>2</sup>	0.27 / 2.14
Standard dimensions (length / width excluding mirrors / height) in mm	4697 / 1846 / 1371
Width including mirrors in mm	2029
Wheelbase / track width front/rear in mm	2764 / 1587 / 1568
Height of loading edge in mm	669
Luggage capacity in l	450

\* Fuel consumption and CO<sub>2</sub> emission figures given in ranges depend on the tyres/wheels used