

2016 SWITCHBACK™ FLD



Cruising and Touring – Two Bikes in One with No Compromises

Model shown in HDI configuration.

The vehicle models, configurations, options, and accessories pictured or otherwise described in this reference guide may not be available in all countries.



Markets: HDI, APC, AUS, MEX, ENG, JPN

2016 SWITCHBACK™

FLD

MODEL OVERVIEW



MODEL OVERVIEW

The Switchback™ motorcycle gives riders two bikes in one incredible lightweight package. It's a combined custom street cruiser and a competent touring bike. Versatility begins with a quick-detach windshield and detachable, locking, hard saddlebags—throw them on for highway comfort; take them off for boulevard style.

NEW IN 2016

- Paint color option

MODEL UNIQUE FEATURES

Style

- Black powder-coated engine with polished treatment covers
- 2-into-1 chrome exhaust with straight-cut muffler
- Black, 5-Spoke Cast Aluminum wheels with highlighted rims, 18-inch front, 17-inch rear
- Full coverage front and rear fenders
- Chrome, retro-style headlamp nacelle
- Chrome fork covers
- Chrome tank console with 127 mm speedometer, integrated ignition switch and trim strip
- Black battery box cover with clean styling

MODEL UNIQUE FEATURES *(continued)*

Fit

- Stainless steel, mini ape-hanger handlebar
- Full-length rider footboards with foot controls; standard passenger footpegs
- One-piece, two-up seat with custom stitching
- 695 mm seat height

Function

- H-D® Detachables™, injection-molded, locking, rigid saddlebags
 - Hinge and latching system allow full saddlebag access without intrusion
 - Color-matched to vehicle
 - Styled specifically for clean look when detached
 - Saddlebag locks common with ignition key
- H-D® Detachables™ windshield
- Tank-mounted electronic speedometer with odometer, time-of-day clock on odometer, dual tripmeter, RPM/gear display, fuel gauge with low-fuel warning light and countdown feature, low oil pressure indicator light, engine diagnostics readout, LED indicator lights
- Start, engine cutoff, left/right turn signals, horn, hi/low beam with flash-to-pass hand controls
- Self-canceling turn signal controls with integrated hazard warning
- Barrel key, tank console-counted ignition; fork lock common with ignition key
- 17.8 L fuel tank
- Advanced suspension for ride comfort and competent handling
 - 41.3 mm front forks with cartridge valve dampening
 - Preload adjustable rear shocks with oil emulsion damping control and retro cigar-tube covers

MODEL UNIQUE FEATURES *(continued)*

Performance

- Rubber-mounted, Air-cooled, 1690 cc Twin Cam 103™ engine
- 6-Speed Cruise Drive® transmission
- Electronic Sequential Port Fuel Injection (ESPFI) with heated O2 sensors
- Anti-lock Braking System (ABS)¹ standard

AVAILABLE OPTIONS

- Smart Security System² with proximity-based, hands-free security fob (factory installed option)
- Engine Idle Temperature Management Strategy (EITMS) (dealer-activated option)

¹ Harley-Davidson's independent Anti-lock Braking System is designed to help you maintain control during braking events, especially those that happen in less than optimum conditions. Engineering and styling worked together to make sure the system is not only designed and carefully tested to work superbly, but that it is also engineered not to interfere with style.

² North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

2016 SWITCHBACK™

FLD

MODEL SPECIFICATIONS¹



Specifications apply to all available markets unless noted.

DIMENSIONS	
Length	2360 mm (92.9 in.)
Overall Width	930 mm (36.6 in.)
Overall Height	1385 mm (54.5 in.)
Seat Height <i>(unladen)</i>	695 mm (27.4 in.)
Ground Clearance	110 mm (4.3 in.)
Rake <i>(steering head)</i>	29.9°
Fork Angle	28.9°
Trail	148 mm (5.8 in.)
Wheelbase	1595 mm (62.8 in.)
Tires <i>(Dunlop® Harley-Davidson® Series, bias blackwall front and rear):</i>	
• Front – D402F	130/70B18 63H
• Rear – D401	160/70B17 73H
Fuel Capacity	17.8 L (4.7 gal.) <i>(warning light at approximately 3.4 L)</i>
Oil Capacity <i>(w/filter)</i>	2.8 L (3 qts.)
Transmission Capacity	.95 L (1 qt.)
Primary Chain Case Capacity	.95 L (1 qt.)
Weight:	
• As Shipped	319 kg (706 lbs.)
• In Running Order	333 kg (734 lbs.)
• Gross Vehicle Weight Rating	530 kg (1170 lbs.)
• Gross Axle Weight Rating:	
• Front	206 kg (455 lbs.)
• Rear	360 kg (794 lbs.)
ENGINE	
Engine	Air-cooled, Twin Cam 103™
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder
Bore x Stroke	98.4 mm x 111.1 mm (3.87 in. x 4.374 in.)
Displacement	1690 cc (103.1 cu. in.)
Compression Ratio	9.6:1
Fuel System ²	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Fiberglass media, washable
Lubrication System	Pressurised, dry-sump

DRIVETRAIN	
Primary Drive	Chain, 34/46 ratio
Final Drive	Belt, 32/66 ratio
Clutch	Multi-plate, wet
Transmission	6-Speed Cruise Drive®
Gear Ratios <i>(overall):</i>	
• 1st	9.311
• 2nd	6.454
• 3rd	4.793
• 4th	3.882
• 5th	3.307
• 6th	2.79
CHASSIS	
Frame	Mild steel, tubular frame; rectangular section backbone; stamped, cast, and forged junctions; forged fender supports; MIG welded
Swingarm	Mild steel, rectangular tube sections backbone; stamped junctions; MIG welded
Front Forks	41.3 mm fork with 20 mm cartridge damping and triple rate spring
Rear Shocks	Nitrogen charged 36 mm monotube damper with 5 step preload adjustable dual rate spring
Wheels ³ :	Black 5-Spoke Cast Aluminum
• Front	18 in. x 3.5 in. (457 mm x 89 mm)
• Rear	17 in. x 4.5 in. (432 mm x 114 mm)
Brakes:	
• Caliper Type	4-piston fixed front, and 2-piston torque-free floating rear
• Rotor Type <i>(diameter x width):</i>	Patented, uniform expansion rotors (floating, front only)
• Front <i>(floating)</i>	300 mm x 5.1 mm (11.8 in. x 0.2 in.)
• Rear	292 mm x 5.1 mm (11.5 in. x 0.2 in.)
• Anti-lock Braking System	Standard
Suspension Travel:	
• Front Wheel	98 mm (3.9 in.)
• Rear Wheel	54 mm (2.1 in.)
PERFORMANCE	
Engine Torque ⁴ :	
• HDI <i>(per EEC/95/1)</i>	126 Nm (92.9 ft-lb) @ 3500 RPM
Lean Angle <i>(per J1168):</i>	
• Right	29°
• Left	29°
Fuel Economy ⁵ <i>(EPA urban/highway test)</i>	5.6 L/100 km (42 mpg)

ELECTRIC	
Battery <i>(per Battery Council International Rating)</i>	Sealed, maintenance-free, 12V, 19-amp/hour, 270 cca
Charging	Three-phase, 40-amp system <i>(493W @ 13.5V, 2000 RPM, 540W max power @ 13.5V)</i>
Starting	1.2kW electric with solenoid shift starter motor engagement
Lights <i>(as per country regulation):</i>	
• Headlamp <i>(Quartz Halogen)</i>	55-watt low beam, 60-watt high beam
• Tail/Stop Lights	5W/21W
• Indicator Lamps ⁶	High beam, neutral, low oil pressure, engine diagnostics, turn signals, low fuel warning, ABS <i>(optional)</i> , low battery, body controller diagnostics, security system ⁶ <i>(HDI only)</i>
WARRANTY	
Warranty	24 months <i>(unlimited mileage)</i>
Service Interval ⁷	First 1600 km (1000 miles), every 8000 km (5000 miles) thereafter

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod® models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Recommended 91 octane or higher fuel (R+M)/2.

³ Standard and optional wheels may vary by country and region.

⁴ Values shown are nominal. Performance may vary by country and region.

⁵ The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

⁶ North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

⁷ Inspections of certain systems and components are required at 4000 km (2500 mile) intervals. See Owner's Manual for full details.

2016 SWITCHBACK™

FLD

COLORS/CALLOUTS



SOLIDS

Vivid Black

Deep Jade Pearl

NEW Velocity Red Sunglo *(shown)*

* Availability of colors may vary from dealer to dealer, and is subject to change without notice.

Model shown in Domestic configuration.

